



City of Port St. Lucie Building Department
 121 SW Port St. Lucie Blvd
 Port St. Lucie, FL 34984
 772-871-5132 • Web Site: <http://www.cityofpsl.com>
 To Schedule Inspections Call: 871-5270

**Re-Roof
 Inspection Affidavit**

Supplemental Fasteners Inspection Affidavit

PERMIT # _____ CONFIRMATION # _____

I, _____, Licensed as a(n):
(print name and check license type)

General Contractor Building Contractor Residential Contractor
 Roofing Contractor Structural Engineer Architect
 Certified Bldg Inspector under F.S. 468
 Property Owner as per F.S. 489.103

License # _____, did personally inspect the **Roof Deck Nailing** **Secondary Water Barrier**

Work on _____ of property located at _____, Port St. Lucie, FL
(Date) (Job Site Address)

All re-roofs regardless of value shall comply with the following:

Re-nailing: All sheathing and decking shall be re-nailed per section 201.1 of the *Hurricane Mitigation Retrofit Manual* and a secondary water barrier installed.

Existing fasteners that are 8d clipped head, round head or ring shank and spaced 6 in. or less o.c. may be counted. Additional fasteners shall be 8d rnk shank nails with round heads spaced at 6 in. o.c. along framing.

Indicate below which method is to be used to satisfy the scndary water barrier requirements. Call out approved product on Product Approval Checklist.

_____ All Joints in roof sheathing shall be covered with a minimum of 4 in. wide strip of self-adhering polymer modified bitumen tape. Wood deck and self-adhering tape shall then be covered by one layer of approved underlayment.

_____ Entire roof deck shall be covered with an approved self-adhering polymer modified bitumen cap sheet. No additional underlayment is required.

_____ The entire roof deck shall be covered with an approved asphalt impregnated 30# felt underlayment installed with nails and tin-tabs as required for the HVHZ. (No additional underlayment shall be required over the top of this sheet.)

_____ Outside of the HVHZ, an underlayment complying with section 1507.2.3 of the Florida Building Code, building fastened as described below or a layer of asphalt impregnated approved #30 felt shall be installed. The felt is to be fastened with 1" round plastic cap or metal cap nails, attached to a nailable deck in a grid pattern of 12 inches (305 mm) staggered between the overlaps, with 6-inch (152 mm) spacing at the overlaps. For slopes of 2:12 to 4:12 an additional layer of felt shall be installed in a single-fashion and lapped 19" and fastened as described above. (No additional underlayment shall be required over the top of this sheet.)

_____ **Exception:** An approved 30# underlayment installed per HVHZ using nails and tin-tabs and covered with an approved self-adhering polymer modified bitumen cap sheet or an approved cap sheet hot-mopped shall be deemed to meet the requirements for secondary water barrier.

Based upon this examination, I have determind that the installation was done according to the Hurricane Mitigation Retrofit Manual (based on F.S. 553.844)

 Signature

 Seal and Date

 Print Name

State of Florida
 County of _____

 Notary Signature

Sworn before me on this _____ day of _____, 20_____
 Personally known _____ Produced ID _____ Type of ID _____